



### FEATURES

- Full-duplex audio speakerphone
- 5" TFT display Full touch-screen with Optical Bonding anti-glare technology for enhanced readability in brightly lit settings
- RJ45 port for directly connecting to the Ethernet
- Local or PoE (Powered over Ethernet) power supply
- Customizable user interface with UI Creator software
- Configurable quick controls (default main entrance door-opener)
- List of AUX commands for activating auxiliary functions
- "Panic" function for emergency calls to the porter (if present on the system)
- Audio video settings: ringtone volume, display brightness, interface backgrounds
- Different ringtones for entry panels and landings
- Exclude ringtone key (the alert LED lights up when silenced)
- Self-inserting video of entry panels with cyclic selection
- Unlimited calls to other receivers and smartphones and tablets
- Contacts list and favorites list
- Video answering service, stores up to 100, 10-second audio and video messages.
- Audio and video recording during conversations
- Sending and receiving text messages from the porter
- Live feeds of the connected IP video cameras
- Business function: for automatic door opening during business hours
- Block display function for cleaning
- Standard SIP protocol, H.264 video codec, G711 audio codec
- On-board web server for configuring and managing via the browser

## XTS 5IP BK 840CH-0100

### TECHNICAL SPECIFICATION

| MODELS                            | XTS 5IP BK      |
|-----------------------------------|-----------------|
| Dimensions (mm)                   | 138 x 98 x 24   |
| Local power supply (V)            | 14 ÷ 18 DC      |
| PoE power supply                  | IEEE 802.3af-PD |
| Consumption in stand-by mode (mA) | 270             |
| Max. absorption (mA)              | 330             |
| Operating temperature (°C)        | 0 ÷ +40         |
| Protection rating (IP)            | 30              |
| Video standard                    | H.264           |
| Colour                            | Black           |

### ARTICLE / CODE      DESCRIPTION

**XTS 5IP BK  
840CH-0100**

**Full-touch video intercom for IP360 system, 5" TFT touch screen display, with Graphical User Interface - black.**

Surface mounted monitor with 5" TFT touch screen display with Optical Bonding technology. User interface for managing video intercom functions, intercom calls, video-messaging, and text messaging. It uses SIP protocol and G711 audio codec and H.264 video codec. RJ45 port for network, PoE or local connection. On-board web server for configuring and updating firmware. It includes bracket for surface mounting on 503 box (horizontal) and Ø 60 mm round box. Ready for flush mounting with dedicated box. Compatible with IP360 system.

