

MTM - MTM VR

Components for modular external units
for X1, XiP, IP360 and GSM systems



FEATURES

- Up to 8 call per single module
- Dual blue or white backlight with brightness settings
- Also programmable manually to handle 8, 4, 3 or 2 calls

MTM8C 60020030

MODELS	MTM8C
Dimensions (mm)	85 x 85 x 35
Packaging dimensions (mm)	156 x 57 x 110
Power supply (V)	10.7 - 18 DC
Max. absorption (mA)	25
Operating temperature (°C)	-25 ÷ +55
Protection rating (IP)	54

ARTICLE / CODE DESCRIPTION

MTM8C
60020030

8-call module.

Electronic module with techno-polymer body, 8 call buttons and 16 LEDs for the double blue or white backlit name tags. Adjustable colour and brightness of the LEDs using the main modules. To finish off with button front-plate. When combined with the corresponding front panel, it guarantees IP54 water and dust protection rating.



Components for modular external units for 200 systems



FEATURES

- Up to 8 call per single module
- Blue backlit name tags

MTM8C/200 60020220

MODELS	MTM8C/200
Dimensions (mm)	85 x 85 x 35
Packaging dimensions (mm)	156 x 57 x 110
Power supply (V)	14 - 18 AC
Consumption in stand-by mode (mA)	15
Max. absorption (mA)	15
Operating temperature (°C)	-25 ÷ +55
Protection rating (IP)	54

ARTICLE / CODE DESCRIPTION

MTM8C/200
60020220

8-call module for 200 systems.

Electronic module with techno-polymer body, 8 call buttons and 8 LEDs for the double blue or white backlit name tags. Compatible only with the MTM8C/200 call module for 200 systems. To finish off with button front-plate. When combined with the corresponding front panel, it guarantees IP54 water and dust protection rating.

