MTM – MTM VR Components for modular external units for X1, XIP, IP360 and GSM systems

FEATURES

- Play back multi-language voice messages
- On-board teleloop for hearing aid patients
- Easy manual and/or PC-based programming



MTMBFVS 60020390

MODELS	MTMBFVS	
Dimensions (mm)	85 x 85 x 35	
Packaging dimensions (mm)	156 x 57 x 110	
Power supply (V)	10.7-18 DC	
Consumption in stand-by mode (mA)	20	
Max. absorption (mA)	55	
Operating temperature (°C)	-25 ÷ +55	
Protection rating (IP)	54	

ARTICLE / CODE DESCRIPTION

MTMBFVS 60020390

Hearing impaired and voice synthesis module

Electronic module with techno-polymer body, equipped with a loudspeaker used for the playing back system voice messages. It has an audio-frequency induction system for hearing aids, in the "T" position. To finish off with the hearing impaired module. When combined with the corresponding front panel, it guarantees IP54 water and dust protection rating.





FEATURES

• Dual blue or white backlight with brightness settings





MODELS	мтммі
Dimensions (mm)	85 x 85 x 35
Packaging dimensions (mm)	156 x 57 x 110
Power supply (V)	10.7-18 DC
Max. absorption (mA)	25
Operating temperature (°C)	-25 ÷ +55

ARTICLE / CODE DESCRIPTION

MTMMI 60020290

Information module.

Electronic module with techno-polymer body equipped with LED for the double blue or white backlighting of the information tag. It allows to adjust colour and brightness by using the main modules. To finish off with information module front-plate. When combined with the corresponding front panel, it guarantees IP54 water and dust protection rating.

