



FEATURES

- 2 call buttons
- 2 on-board controls: electric lock and auxiliary control (1A, 30V max)
- LED pictograms for status alerts: door opening, active communication, call in progress and system busy
- Adjustable speaker, microphone and electric lock
- Dual blue or white backlit name tags with brightness settings
- Water and dust protection rating IP54
- MiniUSB front panel for firmware updating and programming.



MTMA/08 60020420

TECHNICAL SPECIFICATION

| MODELS | MTMA/08 |
|-----------------------------------|----------------|
| Dimensions (mm) | 85 x 85 x 35 |
| Packaging dimensions (mm) | 156 x 57 x 110 |
| Power supply (V) | 14 ÷ 18 DC |
| Consumption in stand-by mode (mA) | 30 |
| Max. absorption (mA) | 70 |
| Operating temperature (°C) | -25 ÷ +55 |
| Protection rating (IP) | 54 |

ARTICLE / CODE DESCRIPTION

MTMA/08
60020420

Intercom modules for XIP systems.

Electronic module with techno-polymer body and 2 call buttons with double, blue or white, namecard backlighting. Featuring a local control for electric lock, auxiliary contact (1A, 30V max), inputs for door lock release button and for door status indication (programmable I/O), output for activation of outdoor cameras (programmable I/O). Dip-switch for adapting the line impedance. The front is equipped with LEDs for visual indication of the system status. It allows to adjust the audio volume of the microphone and speaker and the activation time of the electric lock. Manual or PC programming via MINI USB connector on the front. To be completed with a video intercom front panel. When combined with the corresponding front panel, it guarantees IP54 water and dust protection rating.

